



professional sewing

HENGTAI products ( the structure and advantages of main products)

连续23年亨泰珠边机全球销量第一。  
向您推荐我们引以为豪的自动化产品系列……



HT-ZF1800 全自动毛巾双边纵缝机  
AUTOMATIC DOUBLE SIDE LENGTH HEMMING TOWEL MACHINE

特征

- 操作简便，启动电源，打开程序即可实现无人化操作。
- 智能控制，每一件产品线迹工整，规格精准如一。
- 低耗能，380V电压输入，整机功率2.4KW
- 故障诊断，自动报警，即时发现错误即时纠正。
- 断线检测
- 折边宽度轻松实现大跨度调整。

Features

- Simple operation, it can be run without worker as soon as electric start and procedure begin.
- Intelligent control, the stitch is regular, and specification is accurate for each produce always.
- Low energy consumption, power- 380V/2.4KW,max air pressure- 6KGS;
- Fault diagnosis and warning automatically, it can solve problem automatically immediately when any fault found in operation.
- Off thread check
- There is a great improvement on edge fold width.

|                          |                                  |
|--------------------------|----------------------------------|
| HT-ZF1800 全自动毛巾双边纵缝机技术参数 | 100L工业吸尘器一台                      |
| 可纵缝制毛巾、巾被最大宽度1.8米        | 输入电压380V                         |
| 可缝制毛巾产品最小宽度为260毫米        | 总电流12A                           |
| 配置左、右缝边机各一台              | 总功率4.7kw，洁净压缩空气0.5Mpa-0.6Mpa     |
| 单针、链式缝迹                  | 最高缝纫速度18米/分（变频可调，以16米/分最佳）       |
| 折边器                      | 落布形式一平幅落布                        |
| 自动纠偏,光电自动跟踪              | 摆布长度约1米                          |
| 缝纫时光纤自动跟踪                | 摆布次数一与缝纫速度同步变频可调                 |
| 张力按需电动可调                 | 外形尺寸:4300×2520×3000mm; 气压:0.5Mpa |
| 工作时无布自动停车、断线自动停车         |                                  |
| 触摸屏随机即时机器动态数据,人机对话世界清晰方便 |                                  |

|   |  |
|---|--|
| The Technical Parameter of HT-ZF1800 Automatic Length Hemming Towel Machine   | 100 L An Industrial Vacuum Cleaner   |
| Length Sewing Towel\The maximum width of Towel is 1.8 meters  | Input Voltage 380V   |
| The minimum width of Towel is 260MM   | Total Current 12A  |
| Equipped with the left and right sewing machines of Pegasus   | Total Power 4.7Kw Clean compressed air 0.5Mpa-0.6Mpa   |
| Single Needle Chain Stitching   | Sewing Speed: 18 meters/min( frequency adjustable , 16 meters/minute is best)                  |
| Seventy percent off flanging machine  | Layout form - Flat drop  |
| Automatic correction - photoelectric automatic alignment  | Towel Length : Around 1 meters   |
| Sewing time, fiber automatic alignment  | The number of swinging towels -- Synchronized with sewing speed, variable frequency adjustable |
| The tension is adjustable by the electric power according to demand   | Dimension: 4300×2520×3000mm; Pressure 0.5Mpa   |
| When working, no cloth automatic stop, broken line automatic stop   |  |
| Touch screen displays random, instantaneous machine dynamic data, man-machine dialogue, the world is clear and convenient |  |